


Shield Grooved Reducing Tee



SDG-53

Nominal Size min/in	Pipe O.D. mm	Maximum Working Pressure PSI	C-E mm	Weight kg
2x1/2	60.3x48.3	500	82.5	1.20
30.Dx2	76.1x60.3	500	101.5	1.95
3x2	88.9x60.3	500	106	2.74
3x30.D	88.9x76.1	500	106	2.92
4x1	114.3x53.4	500	127	4.35
4x2	114.3x60.3	500	127	4.80
4x30.D	114.3x76.1	500	127	4.76
4x3	114.3x68.9	500	127	4.94
5/8x30.Dx2	139.7x60.3	500	139.5	6.73
5/8x30.Dx30.D	139.7x76.1	500	139.5	7.29
5/8x30.Dx3	139.7x68.9	500	139.5	7.41
5/8x30.Dx4	139.7x114.3	500	139.5	7.79
5x2	141.3x60.3	500	139.5	6.98
6/8x30.Dx2	165.1x60.3	500	165	10.68
6/8x30.Dx30.D	165.1x76.1	500	165	10.76
6/8x30.Dx3	165.1x68.9	500	165	10.85
6/8x30.Dx4	165.1x114.3	500	165	11.41
6/8x30.Dx5/8x30.D	165.1x139.7	500	165	11.91
6x2 1/2	168.3x73.0	500	165	10.56
6x4	168.3x114.3	500	165	11.66
6x5	168.3x141.3	500	165	12.48
8x2	219.1x60.3	500	197	18.71
8x30.D	219.1x76.1	500	197	18.53
8x3	219.1x68.9	500	197	18.56
8x4	219.1x114.3	500	197	18.18
8x5/8x30.D	219.1x139.7	500	197	16.43
8x6/8x30.D	219.1x165.1	500	197	20.37
10x8/8x30.D	273.0x165.1	500	229	29.25
10x8	273.0x219.1	500	229	30.07
12x8	325.9x219.1	500	254	47.27

SHIELD reserves the right to change the contents without notice • Please refer to UL/FM approvals for details.
Reducing tee SDG-55 (threaded outlet) are also available, contact Shield for details.