


Shield Light Rigid Coupling

SDG-20



Nominal Size in	Pipe O.D. mm	Maximum Working Pressure PSI	Dimensions			Bolt/Nut No. - Size mm	Approx. Weight kg
			X mm	Y mm	Z mm		
2	60.3	300	87.2	122.5	44	2- $\frac{3}{8}$ x2- $\frac{1}{2}$	0.80
2 $\frac{1}{2}$	73.0	300	96.8	138.5	44	2- $\frac{3}{8}$ x2- $\frac{1}{2}$	0.85
3O.D.	76.1	300	100.8	141.5	44	2- $\frac{3}{8}$ x2- $\frac{1}{2}$	0.85
3	88.9	300	113.5	157.5	44	2- $\frac{3}{8}$ x2- $\frac{3}{4}$	1.06
4	114.3	300	142.0	185.5	48	2- $\frac{3}{8}$ x2- $\frac{3}{4}$	1.45
5 $\frac{1}{2}$ O.D.	139.7	300	168.5	225.5	50	2-1x3	2.00
6 $\frac{1}{2}$ O.D.	165.1	300	196.0	252.7	50	2-1x3	2.34
6	168.3	300	198.8	256.5	50	2-1x3	2.34
8	219.1	300	256.0	326.0	58	2- $\frac{1}{2}$ x75	4.03