




Shield - Fire Department Connection

UL Listed.

▲ Model: FD-90

▲ Model: FD-Y



Product Description

Model FDCA (straight pattern) Fire Dept Connections with single clapper 4 x 2 1/2" x 2 1/2" Siamese type. The clapper design allows for one or both inlets to be pressurised during operation and provide supplementary water supply connection for automatic sprinkler systems as per NFPA13. The words "AUTO SPKR" and "F.D.Conn" are cast in raised letters.

Wall Plates

The wall plates are constructed of corrosion resistant aluminium alloy with marking "AUTO SPKR" and "FIRE DEPT CONNECTION".

Optional:

Cast brass plate available upon request.

2 1/2" Brass Coupling (male) with chain are available upon request.

Chrome finish, available upon request.

Approvals:

Straight single clapper siamese: UL Listed 1L06

90 degree single clapper Siamese: UL Listed 1L06

Caps

The breakaway caps are supplied in heavy duty plastic or cast Brass for the protection of 2 1/2" inlets.

Technical Data

Size Outlet 4"(102mm)NPT Female

Inlet 2 1/2"(64mm)NST Male

Maximum working pressure: 300 psi

Test pressure: 600 psi

Standard Finish

FDC-Rough brass

Wall plates-red enamel paint with raised letters painted white Caps-red plastic or red enamel paint

Material Rough Brass C85700 for FDC