



# Shield - Fire Hose Reel



## Kite Marked - BS EN671-1

### ▲ Model: SD FH-19

The Shield Fire Hose Reels are designed and manufactured as per BS EN671-1. Hose Reel drums are made of 1.2mm thickness pre-treated electro-galvanised steel sheet, painted with electrostatic powder coating and oven baked at 180°. Chrome-plated and stainless steel drums are available upon request. Hose Reel drum are ribbed to give extra strength and avoid twisting, Hose used has three ply with two synthetic rubber layers and a textile reinforcement. approved to BS EN-694:2001 with working pressure 12 bar. Every unit is hydrostatically tested to 18 bar pressure. For Automatic Hose Reels the valves open automatically within three revolutions of the reel.



### Product Specifications

Type	Model Number	Size of Hose	Reel Diam. (A mm)	Depth (B mm)	BS Approved
Fixed Manual	SD 19HR-FM	19mm deam. (3/4") Length = 30m	580	205	yes
Fixed Manual	SD 25HR-FM	25mm deam. (1") Length = 30m	580	250	yes
Fixed Automatic	SD 19HR-FA	19mm deam. (3/4") Length = 30m	580	205	yes
Fixed Automatic	SD 25HR-FA	25mm deam. (1") Length = 30m	580	245	yes
Swinging Arm Manual	SD 19HR-SAM	19mm deam. (3/4") Length = 30m	580	195	yes
Swinging Arm Manual	SD 25HR-SAM	25mm deam. (1") Length = 30m	580	220	yes
Swinging Pipe Manual	SD 19HR-SPM	19mm deam. (3/4") Length = 30m	580	185	yes
Swinging Pipe Manual	SD 25HR-SPM	25mm deam. (1") Length = 30m	580	230	yes
Swinging Arm Automatic	SD 19HR-SAA	19mm deam. (3/4") Length = 30m	580	220	yes
Swinging Arm Automatic	SD 25HR-SAA	25mm deam. (1") Length = 30m	580	220	yes
Swinging Pipe Automatic	SD 19HR-SPA	19mm deam. (3/4") Length = 30m	580	235	yes
Swinging Pipe Automatic	SD 25HR-SPA	25mm deam. (1") Length = 30m	580	235	yes